

# CE-5 低压壁挂式储能电池

昆宇电源  
COSPOWERS



- 1 外观极简设计，优雅美观
- 2 防护等级IP40
- 3 支持多电池模组并联，最多可支持8个模块
- 4 简易安装和维护，满足不同客户定制化设计
- 5 多重保护及告警系统，安全可靠

参数 / 型号		CE-5
电池参数	额定电压	51.2V
	电压范围	45~57.6V
	电量	5120Wh
	标准充放电电流	0.25C/0.5C
	最大充放电电流	0.5C/1C
工作条件	电池类型	磷酸铁锂
	工作温度范围	0~45°C
	存储温度范围	-15°C~60°C
	湿度	5%~95%
	冷却方式	自然冷却
	重量	53kg
	尺寸 (W*D*H)	430*186*600mm
	防护等级	IP20
其他	安装方式	壁挂式
	通讯方式	RS485/WIFI (选配)
	匹配逆变器	派能、古瑞瓦特、硕日、固德威、锦浪、鹏城、日月源、Victron、索瑞德、施耐德、SMA、美世乐、拓宝、STUDER



深圳昆宇电源科技有限公司

网址:WWW.COSPOWERS.COM

地址:深圳市宝安区燕罗街道罗田社区第三工业区广田路2号

电话:0755-33185898

版权及最终解释权归深圳昆宇电源科技有限公司所有

## WALL HANGING ENERGY STORAGE POWER SUPPLY



- ① Extreme simple appearance design, elegant and beautiful
- ② Protection class IP40
- ③ It supports multiple battery modules in parallel, up to 8 modules
- ④ Easy installation and maintenance, customized design to meet the requirements of different customers
- ⑤ Multiple protection and alarm system, safe and reliable

Parameters/ Model		CE-5
Battery Parameters	Rated voltage	51.2V
	Voltage range	45~57.6V
	Energy	5120Wh
	Standard Charge/Discharge Current	0.25C/0.5C
	Max. Charge/Discharge Current	0.5C/1C
Working Conditions	Battery Type	LFP
	Operating temperature range	0~45°C
	Storage temperature range	-15°C~60°C
	Humidity	5%~95%
	Cooling Method	Natural cooling
	Weight	53kg
	Size	430*186*600mm
	IP Class	IP20
Others	Installation method	Wall mounting type
	Communication port	RS485/WIFI (Optional)
	Integrated Inverters	Pylon, Growatt, SRNE Solar, Goodwe, Ginlong, Pengcheng, Riyueyuan, Victron, Sorotek, Schneider, SMA, Meishile, TBB, Studer



Shenzhen Coslight Power Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A:No.2,Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T:+86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.