

EnerGalactic-3350 EnerGalactic-3760

昆宇电源
COSPOWERS



全舱温差
<3°C



PACK级消防
高安全性



高能量密度
灵活布置及扩容



模块化预制
无需现场安装

	参数/型号	EnerGalactic-3350	EnerGalactic-3760
电池模块	电芯容量	280Ah	314Ah
	模块成组	1P52S	1P52S
	模块标称电压	166.4V	166.4V
	模块能量	46.592kWh	52.2496kWh
	尺寸(W*D*H)	855*1157*252mm	855*1087*252mm
	防护等级	IP67	IP67
电池簇	模块数量	8pcs	8pcs
	电池簇标称电压	1331.2V	1331.2V
	电压范围	1164.8~1476.8V	1164.8~1476.8V
	单簇能量	372.736kWh	417.997kWh
	电池架尺寸(W*D*H)	972*1157*2480mm	972*1157*2480mm
	防护等级	IP67	IP67
电池舱	电池簇数量	9pcs	9pcs
	电池系统电量	3.355MWh	3.762MWh
	电池舱尺寸	20尺	20尺
	冷却方式	液冷	液冷
	防护等级	IP54	IP54



昆宇电源股份有限公司

网址:WWW.COSPOWERS.COM

地址:山东省东营市东营区东七路28号

电话:0546-7768891

版权及最终解释权归昆宇电源股份有限公司所有

EnerGalactic-3350 EnerGalactic-3760

COSPOWERS



Temperature Difference
inside the Battery
Pack: <math>< 3^{\circ}\text{C}</math>



High Safety Fire
Protection at the
Pack Level



High Energy Density
for Flexible Layout
and Expansion



Modular Prefabrication
No On-site Installation
Required

	Parameters/ Model	EnerGalactic-3350	EnerGalactic-3760
Battery Module	Cell Capacity	280Ah	314Ah
	Battery Pack	1P52S	1P52S
	Module Voltage	166.4V	166.4V
	Module Power	46.592kWh	52.2496kWh
	Size	855*1157*252mm	855*1087*252mm
	IP Class	IP67	IP67
Battery Cluster	NOs.of Modules	8pcs	8pcs
	Cluster Nominal Voltage	1331.2V	1331.2V
	Voltage Range	1164.8~1476.8V	1164.8~1476.8V
	Single Cluster Power	372.736kWh	417.997kWh
	Battery Rack Dimension	972*1157*2480mm	972*1157*2480mm
Battery Cabin	Nos. of Battery Clusters	9pcs	9pcs
	Battery system energy	3.355MWh	3.762MWh
	Battery Cabin Dimension	20-foot	20-foot
	Cooling Method	Liquid cooling	Liquid cooling
	IP Class	IP54	IP54



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Dongying Cospowers Technology Co., Ltd.