



产品容量
提升了 15%+



贯穿式
大 Pack设计



系统循环能效
提升 1%+



支持一字陈列/背靠背排布
节省土地面积 35%

	参数/型号	EnerGalactic-6700
直流侧基本参数	电芯容量	720Ah
	模块成组	1P52S
	单簇模块数量	8pcs
	电池簇数量	7pcs
	电池系统电量	6.709MWh
	额定电网电压	1331.2V DC
	电压范围	1164.8-1476.8V DC
	额定充放电功率	3354kW
系统级参数	工作温度	-30~55°C
	环境湿度	0~95% (无凝露)
	工作海拔	2000m
	通讯方式	以太网、RS485、CAN
	防护等级	IP54
	防盐雾水平	C4(C5可选)
	冷却方式	液冷
	噪音	≤65dB
	消防	七氟丙烷/全氟己酮舱级或气溶胶+水消防+可燃气体探测+防爆通风系统
	尺寸(W*D*H)	2438*6058*2896mm
	重量	55t
符合标准	GB/T 36276, GB/T 34131 UN3536, IEC63056, UL9540	



昆宇电源股份有限公司
 网址: WWW.COSPOWERS.COM
 地址: 山东省东营市东营区东七路28号
 电话: 0546-7768891
 版权及最终解释权归昆宇电源股份有限公司所有



Product capacity is increased by 15%+



Through-go large Pack design



System cycle energy efficiency is increased by 1%+



Support one-line /back-to-back arrangement, saving 35% of land area

Parameters/ Model		EnerGalactic-6700
DC side basic parameters	Cell Capacity	720Ah
	Battery pack	1P52S
	Module quantity in single cluster	8pcs
	Nos. of Battery Clusters	7pcs
	Battery system power	6.709MWh
	Rated AC power	1331.2V DC
	Voltage Range	1164.8-1476.8V DC
	Rated charge and discharge power	3354kW
System level parameters	Operating temperature	-30~55°C
	Ambient Humidity	0~95% (no condensation)
	Working Altitude	2000m
	Communication method	Ethernet, RS485, CAN
	Protection level	IP54
	Anti-salt spray level	C4(C5 optional)
	Cooling Method	Liquid cooling
	Noise	≤65dB
	Fire protection system	Cabin level sevofluoropropane/perfluorohexanone/aerosol + water fire protection + flammable gas detection + explosion-proof ventilation system
	Size (W*D*H)	2438*6058*2896mm
	Weight	55t
Meets standards	GB/T 36276, GB/T 34131 UN3536, IEC63056, UL9540	



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.